
805S



Engine:

■ DOOSAN 4-Zylinder

D34 Stage V Power:

101 kW (135 HP) from 2200 rpm

Max. torque: 500 Nm at 1400 rpm

Displacement: 3,4 liters

Transmission:

• Hydrostatic transmission, Rexroth

2-step NAF transfer gearbox

Axles:

• NAF heavy duty planetary axles

• 100 % selectable differential locks

Brake:

• 2-circuit brake, wet disk brakes

Spring-loaded parking brake

Steering:

44° articulated steering

Tyres:

Size: min. total width
Series: 23,1 x 26 2400 mm
Optional: 18,4 x 26 2200 mm
28L-26 2600 mm

Tank capacity:

Diesel: 160 lHydraulics: 90 lAdBlue: 25 l

Hydraulic system:

Pump output: flow rate: pressure: up to 350 bar
 Hydraulic liquid: series: HLP-46 mineral oil panolin HLP SYNTH with Kleenoil

Microfiltration WGK 1

Cabin:

- Rubber-mounted, soundproofed
- Tested safety cab
- Mechanically suspended comfort seat
- Hot water heating

Elektrics:

- 24 V, 80 A generator
- 2 maintenance-free dry-cell batteries

Instruments:

 Tachometer with operating hour counter, coolant temperature, tank gauge, indicator lights

Winches:

• Series: Adler HY 20-0 (2 x 100 kN) double-drum winch

Max. cable take-up 14 mm, 100 m

without cable equipment!

• Optional: Adler HY 24-0 (2 x 120 kN) double-drum winch

Max. cable take-up 14 mm, 140 m

Adler HY 24-LO (2 x 120 kN) double-drum winch

Max. cable take-up 14 mm, 190 m

Adler HY 32-0 (2 x 160 kN) double-drum winch

Max. cable take-up 14 mm, 150 m

Adler HY 32-LO (2 x 160 kN) double-drum winch

Max. cable take-up 14 mm, 190 m TCM 16+ (2 x 160 kN) double-drum winch Max. cable take-up 14 mm, 220 m

Weight:

• 9.300 kg (series)

Weight distribution: Front axle: 60 %

Rear axle: 40 %

Standard equipment:

2200 mm wide front polder shield, lowerable straight shield
 2200 mm wide, fire extinguisher, first-aid kit, warning triangle,
 tool set

Special equipment:

• Radio control, cable winch, wireless driving, clamping arms for front shield, steering with joystick, road lighting set